


**Advanced Hardware Hacking
Techniques**

**DEFCON 12
Friday, July 30**

Joe Grand (Kingpin)
joe@grandideastudio.com


Agenda

- The "What" and "Why" of Hardware Hacking
- Enclosure & Mechanical Attacks
- Electrical Attacks
- Final Thoughts and Conclusions

2 © 2004 Grand Idea Studio, Inc. 

What is Hardware Hacking (to me)?

- Doing something with a piece of hardware that has never been done before
 - Personalization and customization (e.g., "hot rodding for geeks")
 - Adding functionality
 - Capacity or performance increase
 - Defeating protection and security mechanisms (**not** for profit)
- Creating something extraordinary
- Harming nobody in the process

3 © 2004 Grand Idea Studio, Inc. 

Why Hardware Hacking?

- Curiosity
 - To see how things work
- Improvement and Innovation
 - Make products better/cooler
 - Some products are sold to you intentionally limited or "crippled"
- Consumer Protection
 - I don't trust glossy marketing brochures...do you?

4

© 2004 Grand Idea Studio, Inc. 

Hardware Security Myths

- Many security-related products rely on misconceptions to remain "secure"
- Hardware hacking is hard
- Consumers lack the competency or courage to void their warranty
- Therefore, hardware is "safe"

5

© 2004 Grand Idea Studio, Inc. 

Gaining Access to a Product

- Purchase
 - Buy the product from a retail outlet (with cash)
- Evaluation
 - Rent or borrow the product
- Active
 - Product is in active operation, not owned by attacker
- Remote Access
 - No physical access to product, attacks launched remotely

6

© 2004 Grand Idea Studio, Inc. 

Attack Vectors

- Interception (or Eavesdropping)
 - Gain access to protected information without opening the product
- Interruption (or Fault Generation)
 - Preventing the product from functioning normally
- Modification
 - Tampering with the product, typically invasive
- Fabrication
 - Creating counterfeit assets of a product

7

© 2004 Grand Idea Studio, Inc. 

Enclosure & Mechanical Attacks


- Opening Housings
- External Interfaces
- Anti-Tamper Mechanisms
- Conformal Coating and Epoxy Encapsulation Removal

8

© 2004 Grand Idea Studio, Inc. 

Opening Housings

- Goal is to get access to internal circuitry
- Usually as easy as loosening some screws or prying open the device




9

© 2004 Grand Idea Studio, Inc. 

Opening Housings 2

- If glue is used to seal housing, use heat gun to soften glue and pry open with a knife
 - Some designers use glue with a high-melting point - enclosure will melt/deform before the glue does
- Some devices are sonically-welded to create a one-piece outer shell
 - If done properly, will require destruction of device in order to open it




10

© 2004 Grand Idea Studio, Inc. 

Opening Housings 3

- Security bits and one-way screws
 - Used to prevent housings from being easily opened
 - Ex.: Bathroom stalls, 3.8mm and 4.5mm security bit for Nintendo and Sega game cartridges/systems
 - To identify a particular bit type, visit www.lara.com/reviews/screwtypes.htm
 - Bits available at electronics stores, swapmeets, online



11

© 2004 Grand Idea Studio, Inc. 

External Interfaces


- Usually a product's lifeline to the outside world
 - Manufacturing tests, field programming/upgrading, peripheral connections
 - Ex.: JTAG, RS232, USB, Firewire, Ethernet
- Wireless interfaces also at risk (though not discussed here)
 - Ex.: 802.11b, Bluetooth
- Any interface that connects to a third-party may contain information that is useful for an attack
 - Could possibly obtain data, secrets, etc.


12

© 2004 Grand Idea Studio, Inc. 

External Interfaces 2


- Look for obfuscated interfaces
 - Ex.: Proprietary or out-of-the-ordinary connector types, hidden access doors or holes
- Many times, test points just hidden by a sticker



13 © 2004 Grand Idea Studio, Inc. 


External Interfaces 3

- Use multimeter or oscilloscope to probe and determine functionality
 - Logic state of pins can help with an educated guess
 - Ex.: Pull pins high or low, observe results, repeat
- Monitor communications using H/W or S/W-based protocol analyzer
 - USB: SnoopyPro
 - RS232 and parallel port: PortMon
- Send intentionally malformed/bad packets to cause a fault
 - If firmware doesn't handle this right, device could trigger unintended operation useful for an attack

14 © 2004 Grand Idea Studio, Inc. 

External Interfaces: Backdoors

- Architecture-specific debug and test interfaces (usually undocumented)
- Diagnostic serial ports
 - Provides information about system, could also be used for administration
 - Ex.: Intel NetStructure crypto accelerator administrator access [1]
- Developer's backdoors
 - Commonly seen on networking equipment, telephone switches
 - Ex.: Palm OS debug mode [2]
 - Ex.: Sega Dreamcast CD-ROM boot

15 © 2004 Grand Idea Studio, Inc. 

External Interfaces: JTAG

- JTAG (IEEE 1149.1) interface is often the Achilles' heel
- Industry-standard interface for testing and debugging
 - Ex.: System-level testing, boundary-scanning, and low-level testing of dies and components
- Can provide a direct interface to hardware
 - Has become a common attack vector
 - Ex.: Flash memory reprogramming on Pocket PC devices (www.xda-developers.com/jtag)

16

© 2004 Grand Idea Studio, Inc.



External Interfaces: JTAG 2

- Five connections (4 required, 1 optional):
 - ← TDO = Data Out (from target device)
 - TDI = Data In (to target device)
 - TMS = Test Mode Select
 - TCK = Test Clock
 - /TRST = Test Reset (optional)
- H/W interface to PC can be built with a few dollars of off-the-shelf components
 - Ex.: www.lart.tudelft.nl/projects/jtag,
<http://jtag-arm9.sourceforge.net/circuit.txt>, Or
ftp://www.keith-koep.com/pub/arm-tools/jtag/jtag05_sch.pdf

17

© 2004 Grand Idea Studio, Inc.



External Interfaces: JTAG 3

- JTAG Tools (<http://openwince.sourceforge.net/jtag>) serves as the S/W interface on the PC
- Removing JTAG functionality from a device is difficult
 - Designers usually obfuscate traces, cut traces, or blow fuses, all of which can be repaired by an attacker

18

© 2004 Grand Idea Studio, Inc.



Anti-Tamper Mechanisms

- Primary facet of physical security for embedded systems
- Attempts to prevent unauthorized physical or electronic tampering against the product
- Most effectively used in layers
- Possibly bypassed with knowledge of method
 - Purchase one or two devices to serve as "sacrificial lambs"

19

© 2004 Grand Idea Studio, Inc. 

Anti-Tamper Mechanisms 2

- Tamper Resistance
 - Specialized materials used to make tampering difficult
 - Ex.: One-way screws, epoxy encapsulation, sealed housings
- Tamper Evidence
 - Ensure that there is visible evidence left behind by tampering
 - Only successful if a process is in place to check for deformity
 - Ex.: Passive detectors (seals, tapes, glues), special enclosure finishes (brittle packages, crazed aluminum, bleeding paint)

20

© 2004 Grand Idea Studio, Inc. 

Anti-Tamper Mechanisms 3

- Tamper Detection
 - Enable the hardware device to be aware of tampering
 - Switches: Detect the opening of a device, breach of security boundary, or movement of a component
 - Sensors: Detect an operational or environmental change
 - Circuitry: Detect a puncture, break, or attempted modification of the security envelope

21

© 2004 Grand Idea Studio, Inc. 

Anti-Tamper Mechanisms 4

- Tamper Response
 - Countermeasures taken upon the detection of tampering
 - Ex.: Zeroize critical memory, shutdown/disable/destroy device, enable logging features
- *Physical Security Devices for Computer Subsystems* [3] provides comprehensive attacks and countermeasures
 - Ex.: Probing, machining, electrical attacks, physical barriers, tamper evident solutions, sensors, response technologies



22

© 2004 Grand Idea Studio, Inc.



Conformal Coating and Epoxy Encapsulation Removal

- Encapsulation used to protect circuitry from moisture, dust, mold, corrosion, or arcing
- Epoxy or urethane coatings leave a hard, difficult to remove film



23

© 2004 Grand Idea Studio, Inc.



Conformal Coating and Epoxy Encapsulation Removal 2

- The good news: The coatings are not specifically designed for security
 - Can usually be bypassed with special chemicals like MG Chemicals' 8310 Conformal Coating Stripper (www.mgchemicals.com)
- Brute force approach: Dremel tool and wooden skewer as a drill bit
 - Doesn't damage the components underneath coating
 - Might remove the soldermask, but not a big deal...


24

© 2004 Grand Idea Studio, Inc.



Conformal Coating and Epoxy Encapsulation Removal 3

- When all else fails, use X-ray to determine location of components or connections



25

© 2004 Grand Idea Studio, Inc. 

Electrical Attacks

- Surface Mount Devices
- Probing Boards
- Memory and Programmable Logic
- Chip Delidding and Die Analysis
- Emissions and Side-Channel Attacks
- Clock and Timing

26

© 2004 Grand Idea Studio, Inc. 

Surface Mount Devices


- Harder to work with than through-hole devices
 - Ex.: Fine-pitched packages, tiny discrete components
 - Don't get discouraged
- Human hands have more resolution than the naked eye can resolve
 - A microscope can go a long way to solder components
- Circuit Cellar, July 2004: Build your own computer-controlled, temperature-adjusting SMT oven

27

© 2004 Grand Idea Studio, Inc. 

Surface Mount Devices 2

- Easy to desolder using ChipQuik SMD Removal Kit (www.chipquik.com)



28

© 2004 Grand Idea Studio, Inc. 

Probing Boards


- Look for test points and exposed traces/bus lines
- Surface mount leads and points are usually too small to manually probe
- Many ways to access:
 - Solder probe wire onto board using microscope
 - Use an SMD micrograbber (\$5-\$50)
 - Use a probe adapter (> \$100) from www.emulation.com, www.ironwoodelectronics.com, or www.advintcorp.com
 - Build your own probe

29

© 2004 Grand Idea Studio, Inc. 

Probing Boards 2

- Ex.: Tap board used to intercept data transfer over Xbox's HyperTransport bus [4]



30

© 2004 Grand Idea Studio, Inc. 

Memory and Programmable Logic

- Most memory is notoriously insecure
 - Not designed with security in mind
 - Serial EEPROMs can be read in-circuit, usually SPI or I²C bus (serial clock and data) [5]
- Difficult to securely and totally erase data from RAM and non-volatile memory [6]
 - Remnants may exist and be retrievable from devices long after power is removed
 - Could be useful to obtain program code, temporary data, crypto keys, etc.

31

© 2004 Grand Idea Studio, Inc. 

Memory and Programmable Logic 2

- SRAM-based FPGAs most vulnerable to attack
 - Must load configuration from external memory
 - Bit stream can be monitored to retrieve entire configuration
- To determine PLD functionality, try an I/O scan attack
 - Cycle through all possible combinations of inputs to determine outputs

32

© 2004 Grand Idea Studio, Inc. 

Memory and Programmable Logic 3


- Security fuses and boot-block protection
 - Enabled for "write-once" access to a memory area or to prevent full read back
 - Usually implemented in any decent design
 - Might be bypassed with die analysis attacks (FIB) or electrical faults [7]
 - Ex.: PIC16C84 attack in which security bit is removed by increasing VCC during repeated write accesses

33

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis

- Analysis of Integrated Circuit (IC) dies is typically the most difficult area for hardware hacking
- With access to the IC die, you can:
 - Retrieve contents of Flash, ROM, FPGAs, other non-volatile devices (firmware and crypto keys stored here)
 - Modify or destroy gates and other silicon structures (e.g., reconnect a security fuse that prevents reading of the device)




34

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis 2

- The good thing is that IC designers make mistakes, so tools are needed
 - Failure analysis
 - Chip repair and inspection
- What tools?
 - Chip Decappers
 - Scanning Electron Microscope (SEM)
 - Voltage Contrast Microscopy
 - Focused Ion Beam (FIB)

35

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis 3

- Equipment available on the used/surplus market
- Access to tools in most any large academic institution
- Reverse engineering and analysis services exist (still high priced, \$10k-\$20k)
 - Can provide functional investigation, extraction, IC simulation, analyze semiconductor processes, etc.
 - Ex.: Semiconductor Insights (www.semiconductor.com) and Chipworks (www.chipworks.com)

36

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis: IC Decapsulation

- Decapsulation tools used to "delid" or "decap" the top of the IC housing
- Uses chemical or mechanical means (or both)
- Will keep the silicon die intact while removing the outer material
- Ex.: Nippon Scientific (www.nscnet.co.jp/e), Nisene Technology Group (www.nisene.com), ULTRA TEC Manufacturing (www.ultratecusa.com), approx. \$30k new, \$15k used


37

© 2004 Grand Idea Studio, Inc.



Chip Decapping and Die Analysis: Scanning Electron Microscope

- Used to perform sub-micron inspection of the physical die
- Metal or other material layers might need to be de-processed before access to gate structures
- Depending on ROM size and properties, can visually recreate contents



38


(Photos from ADSR Ltd. and FIB International)

© 2004 Grand Idea Studio, Inc.



Chip Decapping and Die Analysis: Voltage Contrast Microscopy

- Detect variances of voltages and display them as contrast images
 - Performed with a SEM
- Ex.: Could extract information from a Flash ROM storage cell



39

(Photo from <http://testequipmentcanada.com/VoltageContrastPaper.html>)

© 2004 Grand Idea Studio, Inc.



Chip Decapping and Die Analysis: Focused Ion Beams


- Send a focused stream of ions onto the surface of the chip
 - Beam current and optional use of gas/vapor changes the function
- Cutting
 - Ex.: Cut a bond pad or trace from the die (\$1k-\$10k)
- Deposition
 - Ex.: Add a jumper/reconnect a trace on the die (\$1k-\$10k)

40

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis: Focused Ion Beams 2

- Imaging
 - High-resolution image of die structure
- Ex.: Fibics Incorporated (www.fibics.com) or FIB International (www.fibinternational.com)




41

(Photos from Fibics Incorporated)

© 2004 Grand Idea Studio, Inc. 

Chip Decapping and Die Analysis: Focused Ion Beams 3



42

(Photos from Fibics Incorporated)

© 2004 Grand Idea Studio, Inc. 

Emissions and Side-Channel Attacks

- All devices leak information
 - EMI (electromagnetic interference) from circuits (TEMPEST) [8, 9]
 - Power supply fluctuations
 - Visible radiation from LEDs and monitors [10, 11]
- Can be monitored and used by attacker to determine secret information
- Devices may also be susceptible to RF or ESD (immunity)
 - Intentionally injected to cause failure

43

© 2004 Grand Idea Studio, Inc. 

Emissions and Side-Channel Attacks: Power Supply

- Simple Power Analysis (SPA)
 - Attacker directly observes power consumption
 - Varies based on microprocessor operation
 - Easy to identify intensive functions (cryptographic)
- Differential Power Analysis (DPA) [12]
 - Advanced mathematical methods to determine secret information on a device

44

© 2004 Grand Idea Studio, Inc. 

Clock and Timing

- Attacks rely on changing or measuring timing characteristics of the system
- Active (Invasive) timing attacks
 - Vary clock (speed up or slow down) to induce failure or unintended operation
- Passive timing attacks
 - Non-invasive measurements of computation time
 - Different tasks take different amounts of time

45

© 2004 Grand Idea Studio, Inc. 

Security Through Obscurity

- "Security through obscurity" does **not** work
 - Provides a false sense of security to designers/users
 - Might temporarily discourage an attacker, but it only takes one to discover it
- Weak tactics to look out for when hacking "secure" hardware products:
 - Encoded forms of fixed data
 - Scrambled address lines through extra logic
 - Intentionally messy/lousy code
 - Spurious and meaningless data ("signal decoys")

46

© 2004 Grand Idea Studio, Inc. 

Hardware Hacking Challenges

- Advances in chip packaging
 - Ultra-fine pitch and chip-scale packaging (e.g., BGA, COB, CIB)
 - Not as easy to access pins/connections to probe
 - Discrete components can now easily be inhaled
- Highly-integrated chips (sub-micron)
 - Difficult, but not impossible, to probe and modify
- High speed boards
 - Processor and memory bus > hundreds of MHz
 - Serial bus speeds approaching Gigabit/sec.

47

© 2004 Grand Idea Studio, Inc. 

Hardware Hacking Challenges 2

- Cost of equipment
 - Advanced tools still beyond the reach of average hobbyist (probing, decapping, SEMs, etc.)
 - "State of the art" defined by what hackers can find in the trash and at swapmeets
- Societal pressures
 - Hardware hacking is practically mainstream, but "hacker" is still a naughty word

48

© 2004 Grand Idea Studio, Inc. 

Conclusions

- Hardware hacking is approaching a mainstream activity
- Plays an important role in the balance between consumers and corporations (e.g., The Man)
- Think as a designer would
- Nothing is ever 100% secure
 - Given enough time, resources, and motivation, you can break anything
- The possibilities are endless
- Have fun!

49

© 2004 Grand Idea Studio, Inc. 

References

1. J. Grand, et al, "Hack Proofing Your Network: 2nd Edition," Syngress Publishing, 2002, www.grandideastudio.com/files/books/hpyn2e_chapter14.pdf
2. J. Grand (Kingpin), "Palm OS Password Lockout Bypass," March 2001, www.grandideastudio.com/files/security/mobile/palm_backdoor_debug_advisory.txt
3. S.H. Weingart, "Physical Security Devices for Computer Subsystems: A Survey of Attacks and Defenses," *Workshop on Cryptographic Hardware and Embedded Systems*, 2000.
4. A. Huang, "Hacking the Xbox: An Introduction to Reverse Engineering," No Starch Press, 2003.
5. J. Grand (Kingpin), "Attacks on and Countermeasures for USB Hardware Token Devices," *Proceedings of the Fifth Nordic Workshop on Secure IT Systems*, 2000, www.grandideastudio.com/files/security/tokens/usb_hardware_token.pdf
6. P. Gutmann, "Secure Deletion from Magnetic and Solid-State Memory Devices," *Sixth USENIX Security Symposium*, 1996, www.usenix.org/publications/library/proceedings/sec96/full_papers/gutmann/index.html

50

© 2004 Grand Idea Studio, Inc. 

References 2

7. S. Skorobogatov, "Breaking Copy Protection in Microcontrollers," www.cl.cam.ac.uk/~sps32/mcu_lock.html
8. W. van Eck, "Electronic Radiation from Video Display Units: An Eavesdropping Risk?" *Computers and Security*, 1985, www.jya.com/emr.pdf
9. J.R. Rao and P. Rohatgi, "EMPowering Side-Channel Attacks," IBM Research Center, www.research.ibm.com/intsec/emf-paper.ps
10. Joe Loughry and D.A. Umphress, "Information Leakage from Optical Emanations," *ACM Transactions on Information and System Security* v.5, #3, August 2002, www.applied-math.org/optical_tempest.pdf
11. M. Kuhn, "Optical Time-Domain Eavesdropping Risks of CRT Displays," *Proceedings of the 2002 IEEE Symposium on Security and Privacy*, May 2002, www.cl.cam.ac.uk/~mgk25/ieee02-optical.pdf
12. P. Kocher, J. Jaffe, and B. Jun, "Overview of Differential Power Analysis," www.cryptography.com/resources/whitepapers/DPATechInfo.PDF

51

© 2004 Grand Idea Studio, Inc. 

Appendix A: Additional Resources

- J. Grand, et al, "Hardware Hacking: Have Fun While Voiding Your Warranty," Syngress Publishing, January 2004.
- J. Grand, "Practical Secure Hardware Design for Embedded Systems," *Proceedings of the 2004 Embedded Systems Conference, 2004*, www.grandideastudio.com/files/security/hardware/practical_secure_hardware_design.pdf
- A. Huang, "Keeping Secrets in Hardware: the Microsoft Xbox Case Study," *Massachusetts Institute of Technology AI Memo 2002-008*, May 2002, <http://web.mit.edu/bunnie/www/proj/anatak/AIM-2002-008.pdf>
- F. Beck, "Integrated Circuit Failure Analysis - A Guide to Preparation Techniques," John Wiley & Sons, 1998.
- O. Kömmerling and M. Kuhn, "Design Principles for Tamper-Resistant Smartcard Processors," *USENIX Workshop on Smartcard Technology*, 1999, www.cl.cam.ac.uk/~mgk25/sc99-tamper.pdf
- R.G. Johnston and A.R.E. Garcia, "Vulnerability Assessment of Security Seals", *Journal of Security Administration*, 1997, www.securitymanagement.com/library/lan1_00418796.pdf

52

© 2004 Grand Idea Studio, Inc. 

Appendix B: Related Web Sites

- Cambridge University Security Group - TAMPER Laboratory, www.cl.cam.ac.uk/Research/Security/tamper
- Molecular Expressions: Chip Shots Gallery, <http://microscopy.fsu.edu/chipshots/index.html>
- Bill Miller's CircuitBending.com, <http://billtmiller.com/circuitbending>
- Virtual-Hideout.Net, www.virtual-hideout.net
- LinuxDevices.com - The Embedded Linux Portal, www.linuxdevices.com
- Roomba Community - Discussing and Dissecting the Roomba, www.roombacommunity.com
- TiVo Techies, www.tivotechies.com

53

© 2004 Grand Idea Studio, Inc. 

Appendix C: Tools of the Warranty Voiding Trade

- Bright overhead lighting or desk lamp
- Protective gear (mask, goggles, rubber gloves, smock, etc.)
- ESD protection (anti-static mat and wriststrap)
- Screwdrivers
- X-ACTO hobby knife
- Dremel tool
- Needle file set

54

© 2004 Grand Idea Studio, Inc. 

Appendix C: Tools of the Warranty Voiding Trade 2

- Wire brushes
- Sandpaper
- Glue
- Tape
- Cleaning supplies
- Variable-speed cordless drill w/ drill bits
- Heat gun and heat-shrink tubing
- Center punch

55

© 2004 Grand Idea Studio, Inc. 

Appendix C: Tools of the Warranty Voiding Trade 3

- Nibbling tool
- Jigsaw
- Wire stripper/clipper
- Needle-nose pliers
- Tweezers
- Soldering iron w/ accessories (solder sucker, various tips, etc.)
- Basic electronic components

56

© 2004 Grand Idea Studio, Inc. 

Appendix C: Tools of the Warranty Voiding Trade 4

- Microscope
- Digital and analog multimeters
- Adjustable power supply
- Device programmer
- UV EPROM eraser
- PCB etching kit
- Oscilloscope
- Logic Analyzer

57

© 2004 Grand Idea Studio, Inc. 

Appendix D: Where to Obtain the Tools

- The Home Depot (www.homedepot.com)
- Lowe's (www.lowes.com)
- Hobby Lobby (www.hobbylobby.com)
- McMaster-Carr (www.mcmaster.com)
- Radio Shack (www.radioshack.com)
- Digi-Key (www.digikey.com)
- Contact East (www.contacteast.com)
- Test Equity (www.testequity.com)

58

© 2004 Grand Idea Studio, Inc.



Thanks!

Joe Grand (Kingpin)
joe@grandideastudio.com
